



THE MOST EXCLUSIVE RIDE ON THE ROAD.

Stylishly designed, the IC Corporation HC Series easily commands the recognition your passengers deserve. And it will no doubt earn you their appreciation as well. A fully integrated chassis and body streamlines vehicle systems and maintenance. While beneath its sleek appearances, the HC Series houses the powerful performance and unbeatable durability you rely on to get your passengers where they're going.

IC CORPORATION HC SERIES



Exceptional driver ergonomics with easily accessible controls and ample foot room.



Easy under-hood access minimizes maintenance times and extends service intervals.

IC CORPORATION HC SERIES

The IC Corporation HC Series, treating your passengers, and drivers to a luxurious ride that never compromises performance or reliability.



FRAME

158", 169", 193", 217", 254", 291" wheelbase options
GVWR's of 21,500 – 29,800 lbs.

FRONT END

Chrome, full-width aerodynamic bumper
Chrome, styled grille
Easy Tilt 3-piece hood

FRONT AXLE & SUSPENSION

8,000 & 10,000 lb. axle with parabolic taperleaf springs

BRAKES

Hydraulic 4-wheel disc, split system w/ 4-channel ABS, standard
Diamondlife™ 15" x 1.44", dual 2.6" diameter pistons, front rotors and calipers
Diamondlife™ 15" x 1.44", dual 2.6" diameter pistons, rear rotors and calipers
Parking brake, spring actuated, air operated, optional with hydraulic brakes system
Dual, air brake system w/ 4-channel ABS feature, optional

STEERING

TAS-40 steering gear, standard
TAS-66 steering gear, optional
Remote mount 1.5 qt. Reservoir w/ filter life beyond 500,000 miles
Fixed steering column, standard
Tilt column, optional

DRIVELINE

Dana SPL90 Series shafts and joints

EXHAUST

Single horizontal muffler w/ remote catalytic converter, right-side frame-mounted, standard

ELECTRICAL

12-volt Leece Neville alternators, 175 – 270 amps available
BCI Group 31 batteries, 1100 – 1950 CCA's available

PAINT

Base coat/clear coat

ENGINE

International® VT 365, 175 – 230 horsepower, or International® DT 466, 210 – 245 horsepower
Fuel/water separator integral w/ fuel filter
Air cleaner mounted restriction gauge
Aluminum crossflow over-and-under radiator system w/viscous fan drive
Cruise control

TRANSMISSION

Allison 2500 PTS Series 5-speed w/ overdrive, standard
Allison 1000, 2100, 2200, 3000 and B300 Series available

REAR AXLE AND SUSPENSION

13,500 – 19,800 lb. axles
13,500 lb. vari-rate suspension, standard
15,500 – 21,000 lb. vari-rate suspension, optional
12,000 – 15,500 lb. air suspension, optional
Heavy-duty shock absorbers

FUEL TANK

35, 65 gallons, frame rail mount
40 gallon between the rails
65 gallon, between the rails, optional

CAB

International® Blend-Air system
5-gauge cluster w/ visual and audible warning system
Dome light w/ theater dimming feature
Standard Gra-Mag non-suspension high-back driver's seat w/ 3-pt. seat belt
Optional air suspension high-back drivers seat

TIRES AND WHEELS

Standard 225/70R19.5 12-ply load range F w/ steel painted rims
Other tires in 19.5" and 22.5" sizes available
19.5" polished aluminum wheels available

ADDITIONAL OPTIONS

Fog lights
Bendix AD-IP or AD-9 air dryers
Starting motor w/ overcrank protection
Body circuit switches, 6-channel power module
Engine block heater
Borg-Warner Series 790 viscous fan drive
International® Blend-Air HVAC
Right-hand passenger door w/ trim
Deluxe interior trim
Chrome grab handles w/ rubber inserts
Heater shut-off valves
Heated outside mirrors
Power mirrors
Chrome mirrors
Power windows w/ power door locks
Remote keyless entry
Low washer fluid indicator
Exterior lights on with wiper activation
Theft deterrent system
Horn honk alarm w/o park brake apply
Aware™ Vehicle Intelligence System

BODY SPECIFICATIONS

Overall Length Options (Bumper-to-Bumper)
• Up to 38'
Interior Width
• 96 1/2" measured at floor level
Interior Height
• 78" at center of aisle
Exterior Width
• 102" (excluding mirrors)
Exterior Height
• 118" to top of roof (excluding roof-mounted a/c if equipped)
Body Construction
• Steelgard all-steel inner cage structure
• Steel exterior panels
Special Needs
• ADA compliant wheelchair lift for loading and unloading of special needs passengers
• Customized seat plans to meet numerous market needs

For more information, visit www.ic-corp.com or call 1-800-892-7761

Specifications, descriptions and illustrative material in this literature are as accurate as known at time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment. IC Corporation and the IC Corporation Shield are registered trademarks of IC Corporation.

©2006 IC Corporation, Warrenville, IL 60555 AD-44496L-1 09/2006 Lithographed in the United States of America



A NAVISTAR COMPANY

IC CORPORATION. BUSES BUILT WITH CARE.