

USB-Link™ 2 Vehicle Interface



Bluetooth® Edition

NQ124034



MAKE THE CONNECTION EASIER AND EVEN BETTER THAN EVER.

The USB-Link™ 2, the next generation vehicle interface from NEXIQ Technologies®, has arrived. Dependable and rugged, the new USB-Link 2 is five times faster than its predecessor. It has sixteen times more random access memory than the old USB-Link, and it supports heavier bus loads on simultaneous channels.

The Bluetooth module supports wireless communication via an enhanced data rate (500K b/s J1939). For even more reliability, we've upgraded the USB connector to a more robust, automotive grade connector with a latching mechanism. The USB-Link 2 is compatible with a wide range of OEM software applications.

Vehicle Network Protocol Support

- CAN / J1939 / ISO15765 – 250K, 500 K, 1M b/s with Auto Baud detection (3 channels)
- Single wire CAN (SWCAN)
- ISO 11898-3 Fault Tolerant CAN (FTCAN)
- J1708
- J1850 VPW (Class 2)
- J1850 PWM (SCP)
- ISO 9141 / KWP2000 (ISO 14230) K/L line
- ALDL 9600 and 8192 baud
- ATEC 160 baud

Operating System Support

- Windows® Vehicle Communication API
 - RP1210 a/b/c
 - J2534 (2004 draft)
 - J2534-1 partial implementation (commercial vehicle-focused)
- PC Operating System Compatibility
 - Windows 7 (32 & 64 bit)
 - Windows 8 (32 & 64 bit)
 - Windows 10 (32 & 64 bit)
- Interfaces to Computing Platforms
 - USB 2.0
 - Bluetooth 2.1 + EDR

Comes With The Following



Latching USB cable
NQ404032



6-and 9-pin Deutsch adapter
NQ493148

Bluetooth® Edition: PN124032

Order today from your International® / IC Bus® dealer.